





Reverse Brush Drop Oil Per Board Oil Pattern Distance 42 40 Multi ul **Reverse Oil Total Volume Oil Total Forward Oil Total** 18.4 mL 6.35 mL 24.75 mL **Tank Configuration Tank A Conditioner FIRE Tank B Conditioner** Multi Tank **ICE**

3 8L 8R 3 50 14 A 75 7.8 13.7 5.9 3750 4 9L 9R 1 50 14 A 23 13.7 15.6 1.9 1150 5 11L 11R 2 50 18 A 38 15.6 20.7 5.1 1900 6 12L 12R 2 50 18 A 34 20.7 25.8 5.1 1700 7 13L 13R 2 50 22 A 30 25.8 32.0 6.2 1500 8 14L 14R 1 50 22 A 13 32.0 35.1 3.1 650
3 8L 8R 3 50 14 A 75 7.8 13.7 5.9 3750 4 9L 9R 1 50 14 A 23 13.7 15.6 1.9 1150 5 11L 11R 2 50 18 A 38 15.6 20.7 5.1 1900 6 12L 12R 2 50 18 A 34 20.7 25.8 5.1 1700 7 13L 13R 2 50 22 A 30 25.8 32.0 6.2 1500 8 14L 14R 1 50 22 A 13 32.0 35.1 3.1 650
4 9L 9R 1 50 14 A 23 13.7 15.6 1.9 1150 5 11L 11R 2 50 18 A 38 15.6 20.7 5.1 1900 6 12L 12R 2 50 18 A 34 20.7 25.8 5.1 1700 7 13L 13R 2 50 22 A 30 25.8 32.0 6.2 1500 8 14L 14R 1 50 22 A 13 32.0 35.1 3.1 650
5 11L 11R 2 50 18 A 38 15.6 20.7 5.1 1900 6 12L 12R 2 50 18 A 34 20.7 25.8 5.1 1700 7 13L 13R 2 50 22 A 30 25.8 32.0 6.2 1500 8 14L 14R 1 50 22 A 13 32.0 35.1 3.1 650
6 12L 12R 2 50 18 A 34 20.7 25.8 5.1 1700 7 13L 13R 2 50 22 A 30 25.8 32.0 6.2 1500 8 14L 14R 1 50 22 A 13 32.0 35.1 3.1 650
7 13L 13R 2 50 22 A 30 25.8 32.0 6.2 1500 8 14L 14R 1 50 22 A 13 32.0 35.1 3.1 650
8 14L 14R 1 50 22 A 13 32.0 35.1 3.1 650
9 2L 2R 0 50 26 A 0 35.1 42.0 6.9 0

1 2L 2R 0 50 30 B 0 42.0 30.0 -12.0 0 2 10L 10R 1 50 26 B 21 30.0 26.4 -3.6 1050 3 9L 9R 1 50 26 B 23 26.4 22.8 -3.6 1150 4 7L 7R 2 50 22 B 54 22.8 16.6 -6.2 2700 5 6L 6R 1 50 18 B 29 16.6 14.1 -2.5 1450 6 6L 6R 0 50 14 B 0 14.1 0.0 -14.1 0		START	STOP	LOADS	MICS	SPEED	TANK	CROSSED	START	END	FEET	T.OIL
3 9L 9R 1 50 26 B 23 26.4 22.8 -3.6 1150 4 7L 7R 2 50 22 B 54 22.8 16.6 -6.2 2700 5 6L 6R 1 50 18 B 29 16.6 14.1 -2.5 1450	1	2L	2R	0	50	30	В	0	42.0	30.0	-12.0	0
4 7L 7R 2 50 22 B 54 22.8 16.6 -6.2 2700 5 6L 6R 1 50 18 B 29 16.6 14.1 -2.5 1450	2	10L	10R	1	50	26	В	21	30.0	26.4	-3.6	1050
5 6L 6R 1 50 18 B 29 16.6 14.1 -2.5 1450	3	9L	9R	1	50	26	В	23	26.4	22.8	-3.6	1150
	4	7L	7R	2	50	22	В	54	22.8	16.6	-6.2	2700
6 6 1 6 R 0 5 0 14 B 0 14 1 0 0 - 14 1 0	5	6L	6R	1	50	18	В	29	16.6	14.1	-2.5	1450
	6	6L	6R	0	50	14	В	0	14.1	0.0	-14.1	0

leaner Ratio Main Mix	NA	Forward	
leaner Ratio Back End Mix	NA	Reverse	
leaner Ratio Back End Distance	NA	Combined	
Suffer RPM: 4 = 700 3 = 500 2 = 20	00 1 = 100		

Item	3L-7L:18L-18R	8L-12L:18L-18R	13L-17L:18L-18R	18L-18R:17R-13R	18L-18R:12R-8R	18L-18R:7R-3R
Description	Outside:Middle	Middle:Middle	Inside:Middle	Mlddle: Inside	Middle:Middle	Middle:Outside
Track Zone Ratio	618	146	1.01	1.01	146	618



